



## Advantium 1 *PLUS* Remote Alarm

### Features

- One Input channel
- One Output Channels
- Dry contact relay output
- Normally Open or Normally Closed output capability
- Highly visible lighted status notification
- Distinctive audible notification
- Auto-reset when cylinders are replenished
- Audible Alarm Silence feature
- Ability to “Daisy Chain” multiple alarms
- Switch selectable 40-minute alarm delay
- Convenient on/off switch
- Integrated power supply
- Optional Intrinsic Safety Barriers available for hazardous environments



### Specifications

- **Audio**  
93db audible alarm
- **Power**  
120 VAC or 220 VAC  
50/60 Hz
- **Outputs**  
1 channel  
Dry Contacts  
Normally Open/Normally Closed (jumper selectable)  
Contact Rating .5A 24V
- **Inputs**  
1 channel  
Accepts Normally Open/Normally Closed contact closure (selectable)  
Resettable fuse protection
- **Connectors**  
Input: 6 pin circular  
Output: 4 pin circular
- **Dimensions**  
4 3/4”h x 7 1/2” w x 2 5/8” d

### Ordering Information

Series	Description
575-0011-01-000	Advantium 1 Remote Alarm (120V)
575-0012-01-000	Advantium 1 Remote Alarm (220V)
529-5313	529-5313 Intrinsic Safety Barriers for Protocol Station
529-5316-XX	Input Cable Assembly available in 3', 10', 25', 50' and 100' lengths. "XX" in stock number denotes length.
529-5329-XX	Interconnect Cable Assembly available in 3', 10', 25', 50' and 100' lengths. "XX" in stock number denotes length.